





Kit: Hybrid Pole, Base, Cassette and Carry bag



Twist out the stabilising foot from the base. Turn unit over.



Open up the bungee part of the pole and lock together, then twist out the telescopic part to desired height.
Twist clockwise to lock, anti clockwise to unlock
Insert the pole into foot.



Lift the top rail to raise the graphic from the base. Lean the banner backwards and continue to extend the graphic. Secure the graphic into position by locating the top rail onto the pole.

Important: Hold the top rail whilst lowering the banner to prevent damage to the graphic. (do not drop)



After fitting, the graphic should be left for 24 hours before use to ensure the adhesive bonds sufficiently. Opening the cassette may invalidate the product warranty.

*Graphic tension may be re-applied or added to by turning the ratchet tensioner clockwise; 6 clicks of the ratchet tensioner equal 1 revolution of the banner stand spring. (NB Units are supplied pre-tensioned)

hardware specifications	graphic specifications	additional info
<p>Hardware Dimensions (mm): 2200 max (h) x 860 (w) x 370 (d) approx. 86.6" (h) x 33.9" (w) x 14.6" (d) approx.</p> <p>Base Dimensions (mm): 95 (h) x 860 (w) x 370 (d) approx. 3.7" (h) x 33.9" (w) x 14.6" (d) approx.</p> <p>Weight: 4kg (8.8lbs) approx (including carry bag)</p> <p>Included in kit: Base, top rail, cassette, hybrid pole and carry bag</p>	<p>Visible Graphic Dimensions (mm): 2100 max (h) x 800 or 1000 (w) 82.6" max (h) x 31.5" or 39.4" (w) 1460 min (h) x 800 or 1000 (w) 57.5" min (h) x 31.5" or 39.4" (w)</p> <p>Substrate: Add 300mm (12") to base of graphic to allow for roller mechanism</p> <p>Recommended material thickness 225 - 450 microns (8.86 - 17.72 Mils)</p>	<p>Branding strip</p> <p>Overall Dimensions (mm): 24 (h) x 830 or 1030 (w) 0.94" (h) x 32.7" or 40.6" (w)</p> <p>Visible Dimensions (mm): 20 (h) x 830 or 1030 (w) 0.79" (h) x 32.7" or 40.6" (w)</p> <p>Recommended material thickness: 250 Microns (9.85 Mils)</p>

We are continually improving and modifying our product range and reserve the right to vary the specifications without prior notice. All dimensions and weights quoted are approximate and we accept no responsibility for variance. E&OE.